

AQUA - Waterproof Laminate Floor

Technical Specification Data

Waterproof Floor - Aqua Collection

SKU#	AF2006 Magnolia Oak, AF2009 Navajo Oak, AF2011 Slategray Oak, AF2041 Wheat Oak	
Use	Residential & Commercial	
Water Proof	100% Waterproof	
Size	48"(L) x 7.7"(W) x 8mm(T)	
Material	100% wood fiber, degradable & recyclable	
Thickness	8mm	
Wear Layer	AC4	
Embossing:	Embossed in Register(EIR)	
Bevel type:	Painted bevel edge	
Locking System	Unilin Angle Angle	
Installation	Locking system	
Planks/Carton	8pcs	
Sq. Ft./Carton	20.40 sq.ft.	
Cartons Per Pallet	70 Cartons	
ASTM Test Results		
Test	Test Result	Requirements
Critical radiant flux	1.06 W/cm ²	ASTM E648
Formaldehyde Emission	0.06ppm	ASTM D6007-14
Dimensional stability and Curling	meets or exceeds	ASTM F2199-18
Large Ball Impact Resistance	NOT CRACK	NALFA LF 01-2011
Small Ball Impact Resistance	NOT CRACK	NALFA LF 01-2011
Locking Strength	meets or exceeds	ISO 24334:2014
Scratch Resistance	No visible scratch	ISO 1518-1:2019
Slip Resistance	PASS	NALFA LF 01-2011, ASTM D2394-2017
Thickness Swell	3.50%	NALFA LF 01-2011, ASTM D6007-14
CARB 2	CARB ATCM Phase 2 Compliant	ASTM D6007-14
EPA TSCA TITLE VI	EPA TSCA Title VI Compliant	ASTM D6007-14