



BLACK WHISPER

Rubberized Acoustical Underlayment
for SPC, WPC, Laminate and
Engineered Floating Wood Floors

Specifications

IIC Rating	73
STC Rating	72
Sound Insulation	65%
Water Resistance	Waterproof
Thickness	3.0 mm
Roll Weight	9.75 Lbs + / -
Roll Dimensions	25 ft. Length x 4 ft. Width
Square Footage / Roll	100 SQFT / Roll
Pallet Weight	625 LBS.
Square Footage / Pallet	6,000 SQFT (60 rolls)

Technical Specifications

	Test	Unit	L-400
Compressive Strength	JISK-6767	Mpa	> .035
Tear Strength	JISK-6767	N/M	> 850
Tensile Strength	JISK-6767	Mpa	.0.12
Elongation at Break	JISK-6767	%	> 200
Density	JISK-6767	G/cm3	0.02-0.026
Water Absorption	JISK-6767	G/cm3	0.003
Thermal Conductivity	JISK-6767	W/MK	0.035
Fire Resistance	UL 94 HFI, F.A.R. 25.83		
Salt Resistance		No Change	
Acid Resistance		No Change	
Oil Resistance		No Change	
Alkalinity Resistance		No Change	



DISTRIBUTORS OF:



LAMINATE FLOORS ♦ CERAMIC AND PORCELAIN TILES ♦ UNDERLAYMENTS ♦ MOULDINGS

11701 NW 102nd Rd. Suite 10 ♦ MEDLEY, FL 33178 ♦ TEL: (305) 828-6440 ♦ FAX: (305)828-0452